

HYDRONIC SURFACE Mobile Heater

GENERAC
MAC



HYDRONIC SURFACE

MOBILE HEATER

When it's cold, every second of heat counts. Especially when a frozen pipe or frost hardened ground can set you back hours, days or even weeks. The Generac MAC mobile hydronic heater combines industry-leading BTUs with heavy duty steel construction tough enough to withstand the harshest conditions. All operation of the generator and hydronic system is controlled from a single point: an easy-to-use digital controller.

ADDITIONAL SAFETY ALARMS

- Low HTF volume
- Low fuel
- High temperature
- Low HTF pressure
- All standard engine shutdown features

**NON-TOXIC, ENVIRONMENTALLY
FRIENDLY** heat transfer fluid

110% CONTAINMENT
of system fluids

GENERATOR packaged
within unit for protection and
weather-friendly maintenance

6-ZONE CAPABILITY
provides for greater
use flexibility

LED ROOF STROBE
active while heater is on
for easy working unit
confirmation

**BATTERY ENCLOSURE
& DISCONNECT SWITCH**
included as standard



LOCKABLE UNITS to prevent
theft and vandalism

HIGHEST BTU EFFICIENCY
in its class

**DURABLE, SEALED, HYDRONIC
HOSE CONNECTION** for easy use
and wear/tear protection

FORK AND LIFTING POCKETS
standard, as well as lift bail and lift eyes

SPECIFICATIONS

Additional options available

MAC6000

ENGINE		USA (METRIC)		HEATER	
Make/Brand		Isuzu		Heat Output: BTU	630,000
Model		3CH1		Max Output Temperature	185°F (85°C)
Aspiration		Natural		Temperature Range (Fluid Only)	65°F-185°F (18°C-85°C)
Max Speed (RPM)		3000		Burner Fuel Consumption (100%): gph (Lph)	4.65 (17.6)
Max Engine Power - Standby (HP)		14.9		Burner Make	Riello
Operating Speed (RPM)		1800		Pump Flow @ 61 psi: gpm (Lpm)	4.5 (17)
Operating Engine Power - Standby (HP)		14.9		Pump Max Pressure: psi	65
Operating Engine Power - Prime (HP)		10		Hose Size: in (mm)	0.75 (19.05)
Engine Fuel Consumption - 100% Prime: gph (Lph)	0.72 (2.72)			Max Total Hose Length: ft (m)	3000 (914.4)
Engine Fuel Consumption - 75% prime: gph (Lph)	0.54 (2.15)			Max Individual Hose Length: ft (m)	1500 (457.2)
Engine Fuel Consumption - 50% prime: gph (Lph)	0.36 (1.40)			Number of Zones	6
GENERATOR				Estimated Heater Efficiency	85%
Frequency (Hz)		60		CHASSIS	
UNIT				Number of Axles	2
CSA Listed		YES		Capacity - Axle Rating: lbs (kg)	6000 (2722)
DIMENSIONS				Tire Size: in (mm)	16 (406.4) 235/80 R16
Trailer Mounted (L x W x H): in (m)		180 x 95 x 103 (4.57 x 2.41 x 2.62)		Brakes	Electric; Tow Bar Activated
Dry Weight, Trailer Mounted: lbs (kg)		8440 (3828)		Hitch - Standard: in (mm)	2-5/16 (58.74) Ball Coupler
Operating Weight, Trailer Mounted: lbs (kg)		9820 (4454)		Maximum Tire Pressure (psi)	80
CAPACITY					
Fuel Tank Volume: gal (L)		225 (852)			
HT Fluid Capacity: gal (L)		135 (511)			
Total Maximum Run Time (hrs)		49.6			



APPLICATIONS

- Ground thawing
- Concrete curing
- Frost prevention
- Pipe wrapping in oil fields

When you need it, we bring the heat.



In addition to hydronic heat, Generac Mobile Products offers a full-line of indirect and flameless heaters that are just as tough and easy to use. Learn more at GeneracMobileProducts.com or by calling 800-926-9768 or 920-361-4442.

24/7 • 365 Nationwide Service Support Network;
because when you're on the job, we're on the job.



**Assembled & Built
in the USA**