

FLAMELESS

AIR

Mobile Heaters

GENERAC[®]

MAC



FLAMELESS AIR

MOBILE HEATERS

Generac MAC flameless mobile heaters are specifically designed to safely provide powerful heat in environments in which an open flame could be hazardous. Our patented user interface system is easy to use and allows you to set a temperature that will remain reliable and consistent. And as with all Generac MAC mobile heaters, our flameless heaters are built with safety in mind. Each unit is lockable, provides 110% containment, and the engine is protected because it is never loaded until it is warmed to the ideal level, so that you're never stuck out in the cold.

Software Updates (750F and 950F)

Manual Mode and Auto Mode operations have been optimized to offer more consistent airflow and temperature regulation. Overall heater performance has been enhanced, enabling heaters to reach optimum heat levels faster than ever.

ADDITIONAL SAFETY ALARMS

- Low HTF volume
- Low fuel
- High temperature
- Low HTF pressure
- Positive air shutdown



MAC550F



MAC750F

SPECIFICATIONS

	MAC400FHC	MAC550F	MAC750F	MAC950F
ENGINE				
	USA (METRIC)			
Make/Brand	Isuzu	Isuzu	Isuzu	John Deere
Model	4LE2X S253	4LE2X S253	4JJ1T	4045
EPA Tier	4 Final	4 Final	4 Final	4 Final
Max Speed: rpm	2500	2500	2000	2200
Max Engine Power - Standby: hp	62	62	73	139
Operating Engine Power - Standby: hp	2.85 (10.6)	2.85 (10.6)	3.66 (13.86)	7.1 (26.88)
Operating Speed: rpm	2400	2400	2000	2200
CAPACITIES				
Fuel Tank Volume: gal (L)	55 (208.2)	111 (420.18)	160 (605.67)	160 (605.67)
Heat Transfer Fluid Capacity: gal (L)	24 (90.85)	24 (90.85)	25 (94.64)	28 (105.99)
Total Maximum Run Time: hrs	18.8	37.6	47.8	35.8
Fuel Consumption Rate: gph (Lph)	3.2 (12.11)	3.2 (12.11)	3.55 (13.44)	7.1 (26.88)



MAC950F

	MAC400FHC	MAC550F	MAC750F	MAC950F
HEATER				
USA (METRIC)				
Heat Output: BTU*	448,000	448,000	512,400	994,000
Temperature Rise @ X°	180°F (82°C)	180°F (82°C)	180°F (82°C)	180°F (82°C)
Maximum Output Temperature	180°F (82°C)	180°F (82°C)	180°F (82°C)	180°F (82°C)
Duct Diameter: in (mm)	1 x 12 (304.8)	2 x 12 (304.8)	2 x 12 (304.8)	1 x 20 (508)
Duct Length: ft (m)	25 (7.62)	25 (7.62)	25 (7.62)	25 (7.62)
Estimated Heater Efficiency	85%	85%	85%	85%
FAN				
Air Flow: CFM	1400 - 3600	1400 - 3500	2650 - 5500	3000 - 6000
Pressure: in, H2O	9	5	5	5
DIMENSIONS (LxWxH)				
Trailer Mounted: in (m)	120 x 54 x 82 (3.05 x 1.37 x 2.08)	171 x 72 x 81 (4.34 x 1.83 x 2.06)	191 x 72 x 88 (4.85 x 1.83 x 2.24)	191 x 72 x 88 (4.85 x 1.83 x 2.24)
WEIGHT				
Dry Weight, Trailer Mounted: lbs (kg)	4360 (1978)	4480 (2032)	5540 (2513)	6330 (2871)
Operating (Wet) Weight, Trailer Mounted: lbs (kg)	4700 (2132)	5180 (2350)	6400 (2903)	7900 (3583)
CHASSIS				
Number of Axles	1	1	2	2
Capacity - Axle Rating: lbs (kg)	6000 (2722)	6000 (2722)	6000 (2722)	6000 (2722)
Tire Size	4 x 8 x 16 in (101.6 x 203.2 x 406.4 mm)	235/80 R16	235/80 R16	225/75 R15
Maximum Tire Pressure: psi	80	80	80	80
Brakes	Tow Bar Activated	Electric	Electric	Electric
Hitch - Standard: in (mm)	Pintle	2-5/16 (58.74) Ball Coupler	2-5/16 (58.74) Ball Coupler	2-5/16 (58.74) Ball Coupler

* This number has been calculated using the maximum fuel consumption at the full rated horsepower as provided by the engine manufacturer.



APPLICATIONS

- Gas and oil exploration
- Utilities and power plants
- Mining
- Painting and coatings
- Construction
- Pipeline projects
- Pre-warming equipment
- Employee locker areas and housing
- Emergency thawing
- Offshore drilling rigs
- Dehumidification
- Agricultural applications

When you need it, we bring the heat.



In addition to our safe and reliable flameless heaters, Generac Mobile Products offers a full-line of indirect and hydronic heaters that are just as tough and easy to use. Learn more at GeneracMobileProducts.com or by calling 800-926-9768 and 920-361-4442.

24/7 • 365 Nationwide Service Support Network;

because when you're on the job, we're on the job.

LIGHT TOWERS | GENERATORS | PUMPS | HEATERS



**Assembled & Built
in the USA**