

# DIAPHRAGM DEWATERING PUMPS

**GENERAC®**  
MOBILE



# DIAPHRAGM DEWATERING PUMPS

Generac Mobile diaphragm pumps are a durable and reliable solution for removing water in a variety of shallow and muddy applications, including ponds, trenches, ditches and foundations. Diaphragm pumps don't have an impeller shaft or seal that can be damaged by sand or silt. And, because they are self-priming, these pumps will keep running "run dry" even after all water has been removed...then continue pumping when water pools up again. Available in 2 in. (50.8 mm) and 3 in. (76.2 mm) diameter pumps, in gas or electric models. All models come assembled with wheel kits.

## FEATURES

- Handles spherical solids up to 1.7 in (43 mm)
- Heavy-duty cast aluminum parts for lifetime durability
- Dry run without damage to the pump
- Auto-priming intermittent pumping
- Simple design, low maintenance
- Self cleaning water flow



MCP**5515** WT\*  
*Electric-powered*



MCP**5537** WT\*  
*Gasoline Fuel*



MCP**5411** WT\*  
*Electric-powered*

\*T denotes TPE diaphragm material.

# SPECIFICATIONS

GAS				
	MCP5437	MCP5438	MCP5537	MCP5538
USA (METRIC)				
Suction: in (mm)	2 (50.8)	2 (50.8)	3 (76.2)	3 (76.2)
Max Suction Lift: ft (m)	25 (7.62)	25 (7.62)	25 (7.62)	25 (7.62)
Max Discharge Head: ft (m)	25 (7.62)	25 (7.62)	25 (7.62)	25 (7.62)
Engine	Honda® GX160	Honda® GX140	Honda® GX120	Honda® GX160
Max Horsepower (rpm)	4 (3600)	5.5 (3600)	4 (3600)	5.5 (3600)
Fuel Tank Capacity: gal (L)	0.66 (2.5 L)	0.95 (3.6 L)	0.66 (2.5 L)	0.95 (3.6 L)
Continuous Run Time: hr	3	3.3	3	3.3
Start Method	Recoil	Recoil	Recoil	Recoil
Pump Construction	Aluminum	Aluminum	Aluminum	Aluminum
Diaphragm Material* (Standard)	TPE	TPE	TPE	TPE
Shipping Weight: lbs (kg)	141 (64)	146 (66)	145 (65.8)	150 (68)
Net Weight: lbs (kg)	126 (57)	131 (59)	130 (59)	135 (61)
Dimensions: L x W x H				
Wheel Mount: in (cm)	40 x 25 x 23 (102 x 63.5 x 58.4)	40 x 25 x 23 (102 x 63.5 x 58.4)	40 x 30 x 24 (102 x 76.2 x 58.4)	40 x 30 x 24 (102 x 76.2 x 58.4)

ELECTRIC				
	MCP5411-1	MCP5411-3	MCP5515-1	MCP5515-3
USA (METRIC)				
Suction: in (mm)	2 (50.8)	2 (50.8)	3 (76.2)	3 (76.2)
Max Suction Lift: ft (m)	25 (7.62)	25 (7.62)	25 (7.62)	25 (7.62)
Max Discharge Head: ft (m)	25 (7.62)	25 (7.62)	25 (7.62)	25 (7.62)
Motor	TEFC	TEFC	TEFC	TEFC
Frame	56C	56C	56C	56C
Horsepower	1 hp	1 hp	1.5 hp	1.5 hp
Phase	Single	Three	Single	Three
Voltage	115 / 230	230 / 460	115 / 230	230 / 460
Speed: rpm	1750	1750	1750	1750
Pump Construction	Aluminum	Aluminum	Aluminum	Aluminum
Diaphragm Material	TPE	TPE	TPE	TPE
Shipping Weight: lbs (kg)	145 (65.8)	145 (65.8)	150 (68)	150 (68)
Net Weight: lbs (kg)	130 (59)	130 (59)	n/a	n/a
Dimensions: L x W x H				
Wheel Mount: in (cm)	41 x 25 x 23 (104 x 63.5 x 58.4)	41 x 25 x 23 (104 x 63.5 x 58.4)	38 x 30 x 24 (96.5 x 76.2 x 61)	38 x 30 x 24 (96.5 x 76.2 x 61)

\*Diaphragms come standard in thermal plastic elastomer (TPE). Rubber, Neoprene, Buna and Viton diaphragm options available. Specifications and designs are subject to change without notice.

WARNING: Do not use for pumping volatile and flammable liquids.

### Looking for more pump options?

Generac Mobile trash pumps provide a powerful dewatering solution that handles solids up to 3 in. (76.2 mm) in diameter. For more information visit [GeneracMobileProducts.com](http://GeneracMobileProducts.com)

### 24/7 • 365 Nationwide Service Support Network;

because when you're on the job, we're on the job.



**GENERAC®**  
**MOBILE**